

114.95 EUR
incl. 19% VAT, plus shipping

Assemble the perfect small form factor system for all your computing demands with the flexible ZOTAC® H67-ITX WiFi mini-ITX platform. The ZOTAC® H67-ITX WiFi supports socket LGA1155 2nd generation Intel® Core™ family processors with turbocharged Intel® HD Graphics to let users select the perfect amount of processing power for their needs – whether it is dual or quad-core, with or without Intel® HyperThreading™ technology.

Demanding gamers can install a standard PCI Express x16 ZOTAC® graphics card in the H67-ITX WiFi to form a perfect miniature gaming PC that delivers big system power in a miniature form factor. A mix of seven total SATA 6.0 Gb/s, SATA 3.0 Gb/s and eSATA ports with RAID 0, 1, 5 and 10 support on the ZOTAC® H67-ITX WiFi enable users to maximize storage connectivity and complete the ultimate home theatre PC or home file server.

Product Name	
Product Name	ZOTAC H67-ITX WiFi
Model	
Model	H67ITX-C-E
Chipset	
Manufacturer	Intel
Chipset	H67 Express (B3)
GPU	Intel® HD Graphics ready
CPU Compatibility	
Name	2nd Generation Intel® Core™ i3 i5 & i7 Intel® HD Graphics 2000/3000 ready
Socket	LGA1155
Bus	N/A
Memory	
Memory Type	DDR3
Memory Speed	1066/1333 MHz
Slots	2 x 240-pin DIMM
Capacity	Up to 16GB
CPU and Memory Compatibility List	
CPU and Memory Compatibility List	see above
3D API	
DirectX	DirectX® 10.1
OpenGL	OpenGL® 2.1
Expansion	
Slots	1 x PCI Express x16

Networking	
Ethernet	10/100/1000Mbps
WiFi	802.11n/g/b (300Mb/s)
Audio	
AN/Alog	8-ch HD
Digital	Optical S/PDIF and HDMI outputs
Ports	
DVI	1 (HDCP)
HDMI	1 (1080p w/8-ch audio)
Display Port	1
VGA	1 (w/Adapter)
SATA	2 (SATA 6.0 Gb/s)
	4 SATA 3.0 Gb/s (w/RAID 0 / 1 / 0+1 / 5)
eSATA	1 (SATA 3.0 Gb/s)
PATA	N/A
PS/2	1
Serial Port	N/A
USB Ports	8 x USB 2.0 (4 on back panel / 4 via pin header)
	4 x USB 3.0 (2 onback panel / 2 via pin header)
	8 USB 2.0 ports (4 on back panel / 4 via header)
FireWire Ports	N/A
Cooler	
Cooler	Passive (no fan)
Form Factor	
Form Factor	mini-ITX
OS Compatibility	
Windows	Windows® Vista / 7 Premum ready
General	
SLI Supported	No
Maximum Resolution	2048 x 1536
Other	
Wake-On Support	Wake-on USB
	Wake-on-LAN
Overclocking features	No
Packaging	
Package Contents	4 x SATA cables
	1 x 4-pin CPU power extension cable
	1 x DVI-to-VGA adapter
	1 x I/O back plate
	2 x WiFi antennas
	1 x USB 3.0 header (full-size bracket)
	1 x USB 3.0 low-profile bracket
Graphics Output	1 DVI / 1 HDMI / 1VGA / 1 DP