



469.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Bay Trail !
- -40 - 70°C !
- 9-24V DC !
- All-aluminium !

Support:  [Datasheet](#)

- Intel® Bay Trail SoC Processor (Default: J1900)
- Support 1 * SO-DIMM DDR3L-1333MHz up to 8GB
- All-aluminum body, produced by casting process
- Operating Temperature: -40 ~ 70° C
- 9~24V DC-in (Lockable type)

MB Model	– MZ93-00B
Part No.	– HBJC386Z9300-J19B – HBJC386Z9300I-J19B (support M.2 ac WiFi)
BIOS	– AMI Flash ROM
CPU/Chipset	– Intel® Bay Trail SoC Processor (Default: J1900)
Memory	– Support 1 * SO-DIMM slots DDR3L-1333MHz up to 8GB
Network	– 2 * Intel i211-IT GbE
Storage	– 1 * M.2 M-key 2242/2280 slot (M2M, support SATA interface)
Expansion	– 1 * M.2 E-key 2230 (M2E, support USB 2.0/PCIex1 interface) – 1 * M.2 B-key 3042 slot (M2B, support USB 3.0 interface)
Rear Panel I/O	– 2 * RJ45 – 1 * DVI-I (Max. Resolution: 1920 * 1200@60Hz) – 1 * HDMI (Max. Resolution: 1920 * 1200@60Hz) – 1 * 8 bit GPIO – 1 * Line out & MIC combo – 1 * DC-in (Lockable type)

Front Panel I/O	– 1 * Power SW + Power LED – 1 * HDD LED , 2 * LAN LED – 1 * SIM Card slot – 4 * COM (COM1_support RS485) – 4 * USB2.0 – 2 * USB3.0
Power Source	– Adapter / AC 90~240V input / DC12V-60W – MB : support DC 9~24V input
Compliance	– CE, FCC, LVD, RoHS, ErP Ready
Temperature	– Operating Temperature: -40 ~ 70° C (Under the condition of using M.2 interface SSD) (The test environment is closed and windless) – Storage Temperature: -40 ~ 80° C – Humidity : 10% ~ 90% RH @40°C (non-condensing)
Dimensions	– 185 (W) x 142 (D) x 60 (H) mm
OS Support	– Windows 10, Linux