



1398.00 EUR

incl. 19% VAT, plus [shipping](#)

- TigerLake i5 !
- 15 Zoll !
- IP65 !
- 12-36V DC !



- 15.0" 350 nits TFT LCD with LED backlight
- 5 Wire Resistive Touch/Anti-Reflection Protection Glass
- Support Open frameless design
- Easy HDD and DARM installation, cableless design
- 12-36V DC-in, with Electrical Over Stress (EOS) and OVP design
- Front bezel meets IP65-rated protection

Display	– IP65, NEMA 4 rugged protection, metal front bezel – 15.0" With LED Backlight – 350 nits – 16.7m display color – 1024 x 768 @60Hz resolution – 178°/178° viewing angle (H/V) – 0.099 x 0.297mm pixel pitch – 4:3 aspect ratio – 1000:1 contrast ratio – 35ms response time
Touch Screen	– 5 wires analog resistive type – 346.0 x 270.0mm ±0.3mm active range – Transparency 80 ±3% – Operating force ■ 100g – Surface Hardness ■ 3H (pressure 750g/45°) – Knock test 10,000,000 times keystrokes
Case	– Aluminum panel – Iron case – White color – Spray paint coating requirement
Main System	– Intel® Tiger Lake i5-1135G7 2.4GHz/QC processor – 2* DDR4 SO-DIMM (Max 64GB) – 256MB SPI Flash ROM – Watchdog Timer 256 levels, 0~255 sec. – OS Support Windows 10 / Linux
Expansion	– 1* M.2 E key (2230) for WIFI – 1* M.2 B key (3042/3052/6570) for 4G/5G Module (4pcs Built in Antenna)
Storage	– 1* 2.5" SATA HDD – 1* M.2 M key (2242/2280, SATA/PCI-Ex4)
I/O Connector	– 2* USB3.2 (Gen. 2) – 4* USB2.0 – 2* RS232/422/485 – 2* RS232 – 16bit GPIO – 1* HDMI – 1* AT/ATX Mode Button – 2* RJ45 (1* Intel® I211AT, 1* Intel® I219LM GbE) – 1* 12~36V DC-in Locking Jack – 1* Power button – 1* 2pin Front Power button
Power Input	– 12~36V DC-in – AC version: 100~240V AC-DC 90W power adapter or – DC version: 12VDC with over current protection fuse
Power Consumption	– 45W
Dimensions	– 378.00 * 294.00 * 60.00mm
Compliance	– CE, FCC, IP65 (Front)
Safety	– Shock: 1ms duration – Vibration: 5~500Hz/1 Grms
Temperature	– Operating: : -10°C ~ 50°C – Storage: -20°C ~ 70°C